

Automotive 7283-8397-40 Yazaki RH Plastic Case Connectors

Our Product Introduction

for more products please visit us on ladyshairextensions.com

Basic Information

- Place of Origin: 00
- Brand Name: 2
- Certification: 3
- Model Number: 7283-1114-30
- Minimum Order Quantity: 100
- Price: Price to be discussed
- Packaging Details: 付款方式
- Delivery Time: 供 能力
- Payment Terms: 期限
- Supply Ability: 常 包装



Product Specification

- Pin: 8pin
- Material: Metal
- Advantages: Waterproof
- Connector: Wire To Wire
- Color: Yellow
- Model: 927366-1
- Metal: Type Iron
- Thickness: 203*193*15cm
- Box Type: Self Erecting Boxes
- Radiation Power: 840~1300MW
- Metal Type: Iron
- Universal Type: Fit For 80% Model Cars' Injectors
- Indian Hair: Yes
- Size: 390x240x185cm
- Hair Styles: Body Wave, Straight

Product Description

Automotive 7283-8397-40 Yazaki RH Plastic Case Connectors

Development trend

At present, global automotive connectors take up around 15% that of connector industry, and they are likely to take up even larger proportion in the future due to the driving of electric automotive products. In terms of product cost structure, the cost of a connector used by automobiles on China is only several hundred Yuan on average; compared with the average cost of a foreign automotive connector, of which the cost of each on average is from 125 dollars to 150 dollars, Chinese automotive connector market still has great development potential.

Product parameter

Product name	Automotive Connector
Material	Housing:PBT+G,PA66+GF; Terminal:Copper Alloy/Brass/Phosphor Bronze.
Size	OEM
Operating Temperature range	-40 ~120
Function	Replacement for Original Brand Cars
MOQ	Small order can be accepted

Main features:

- Security of the push-pull self-latching system;
- Multipole types 2 to 26 contacts;
- Solder or print contacts(straight or elbow);
- High packing density for space savings;
- Multiple key options to avoid cross mating of similar connectors;
- Keying system for connector alignment;
- 360°screening for full EMC shielding;
- Pull-away plugs with lanyards available.

Main Parameters:

Humidity (max): <=95% [at 60 deg C /140 F]
 Vibration: 15 g [10 Hz - 2000 Hz]
 Shock Resistance: 100 g [6 ms]
 Salt Spray Corrosion: >144 hr
 Climatical Category: 50/175/21
 Shielding (min): 75 dB (10 MHz)
 Shielding (min): 40 dB (1 GHz)
 IP Rating: IP50



Ellawig companies



+86-15399918960



service@ellawigss.com



ladyshairextensions.com

Room 501, unit 6, building 20, North Lane, east flower market, Beijing