

Wedding Prom 80W Moving Head Light With Auto Zoom Multicolor Pattern **Mixing**

Basic Information

00 . Place of Origin: . Brand Name: 2 3 · Certification: Model Number: XQ-80 • Minimum Order Quantity: 100 Packaging Details: 付款方式 Delivery Time: 供 能力 • Payment Terms: 期限 Supply Ability: 常 包装



Product Specification

XQ-80 Model:

Voltage: 100 To 240 VAC, 50/60 Hz (auto-ranging)

. Light Source: LED Lamp 80W

Color Wheel: 6 Fixed Colors + White

160W Power:

Ata Connectors: 3-pin XLR Input/output Connection • Size: 8.5 X 6.6 X 12.3 220 X 170 X 311.6 Mm

Weight: 5.5 Kg (12.4 Lb) Metal: Type Iron Metal: Type Iron Thickness: 203*193*15cm 203*193*15cm • Thickness: Box Type: Self Erecting Boxes Self Erecting Boxes Box Type: • Radiation Power: 840~1300MW

Product Description

Wedding Prom 80W Moving Head Light With Auto Zoom Multicolor Pattern Mixing

Product Description:

The XQ-80 is a powerful LED moving head light fixture with features such as a high output 80W 4-in-1 RGBW LED in the center, with a 5-45° motorized zoom for an exceptionally bright wide/narrow beam, and 4* segments (Pixel mappable) LED ring, total 8 0.5W RGBD for extra cool eye candy effect. Infinite Pan and Tilt lets users change everything with Wink's ultra-fast 540°/270° pan and tilt, even exciting infinite moves thanks to its incredible infinite pan and tilt rotation capabilities. It also offers 2 automatic modes, 2 active modes of sound, multiple color presets, virtual color wheel effect, 4-button TFT LCD display, 3-pin DMX in/out, powerCONTM compatible power in/out, and a single 1/4-turn omega mounting bracket.

Quick Details:

Model:	XQ-80
Channel Mode:	11/19/25/35 channels
Light Source Life:	22000 hours
Color Temperature:	6500K
Pan:	540°; 8Bit/16Bit
Tilt:	270°; 8bit/16bit
Controls Screens:	2.0-inch screen LCD touch screen display, screen display, can be flipped 180°
Control Method:	Support DMX512, RDM, automatic operation

Product Features:

80W RGBW High Output 4 in 1 LED

4-segment RGB color ring with 8 0.5W RGB 3-in-1 LEDs

Individual pixel and LED ring control

5-45 degree scalable beam angle

540°/270° tilt + infinite pan and tilt

Fast pan/tilt motor with 16-bit resolution

Built-in automatic and sound activity programs

Multiple static color presets and virtual color wheels

ividitiple static color presets and virtual color wheels

Variable electronic dimming and strobe effect (1-20Hz)

Flicker Free Constant Current LED Driver 3-pin male input and 3-pin female output

AC Power Input/Output Connectors Compatible with Power CON™

Protocol: USITT DMX-512 11/19/25/35 channel DMX mode

2.0-inch TFT color LCD display with 4 touch-sensitive buttons

Specifications:

Pan: 540 degrees (8-16 bit resolution) Tilt: 270 degrees (8-16 bit resolution)

Unlimited pan and tilt

Voltage: 100-240 VAC, 50-60 Hz

Power consumption: 110W, 1.44A, PF: 0.66

Width: 8.5 in(220 mm) Depth: 6.6 in (170 mm) Height: 12.3 in (311.6 mm) Weight: 5.5 kg (12.4 lb)





