



Automatic Security Swing Turnstile Barrier Gate Swing Turnstile Barrier

Our Product Introduction

Basic Information

- Place of Origin: 00
- Brand Name: 2
- Certification: 3
- Minimum Order Quantity: 100
- Packaging Details: 付款方式
- Delivery Time: 供 能力
- Payment Terms: 期限
- Supply Ability: 常 包装



Product Specification

- Lane Width: 550-570mm
- IP: IP54
- Pass Speed: 30 Persons/min
- Power Supply: AC220V/110V,50/60Hz
- Drive Mode: Motor Drive
- Max Power Consumption: 200W
- Opening Time: 0.3S
- Humidity: ≤90% Coagulation Free
- Noise: ≤50dB
- Metal: Type Iron
- Metal: Type Iron
- Thickness: 203*193*15cm
- Box Type: Self Erecting Boxes
- Radiation Power: 840~1300MW
- Metal Type: Iron



More Images



Product Description

Automatic Security Swing Turnstile Barrier Gate Swing Turnstile Barrier

Product description:

The matrix type photoelectric stereoscopic detection technology is adopted to sensitively detect the behaviors that threaten the passageway safety, such as illegal intrusion, reverse passing, tail-gating, and give out alarms through sound, light, etc. The turnstile can be combine with other security systems.

This equipment is integrated with mechanism, electric and micro-controller and various kinds of identification technologies, compatible with IC, ID, bar code, fingerprint reader and so on to provide intelligent control and management to flow control. Durable, anti-rusty. provide orderly passage to people, anti-illegal entry or exit, smooth operation, low noise. arm drops off in condition of emergencies.

Product features:

1. Problem-self-checking function.
2. Arm Turning: Bi-direction.
3. When power off, the arm open automatically, and power on again, the arm will be held automatically.
4. When a valid card is read and the passenger passed, the arm can be delayed to close from 1-60s which can be set in the control panel.
5. Auto-reposition function: After the card is read, the passenger doesn't pass within the regulated time, and the turnstile will cancel the order automatically. And the regulated time can be set by managers.
6. Anti-rush function: if there is no open single, the arm will be held tightly.
7. Stable running with little noise.

Product specification:

Dimension	1200*185*980mm
Material	SUS 304 stainless steel
Motor	Brushless DC motor
Access width	600mm
Access direction	Single birectional/Bi directional
Access speed	30 p/m
Operating temperature	-20 ~70
Power supply input	AC110~220V±10%
Gate reaction time	0.2s
Indication way	Acoustic alarming, LED indicator

Product advantages:

1. he speed gate turnstile is with high-quality DC brushless motor is configured and advanced servo control system is carried to truly achieve precise control, stable performance with no maintenance.
2. Lossless mechanism structure is based on German technology adopted to ensure long lifespan.

FAQ:

Q: Did you system have software interface?

A: Yes. We have our own management software.

Q: How does this system connect the access control?

A: Equipment could link to others by TCP/IP or Wiegand.

Q: Does ticket barcode supported?

A: Yes, many access control method for options. Customized management support.

Q: What will happened if power was cut off?

A: The barrier will open automatically if power cut off.

Q: Is it difficult to install it?

A: Its easy to install and we will offer the installation video.



Ellawig companys



+86-15399918960



service@ellawigss.com



ladyshairextensions.com

Room 501, unit 6, building 20, North Lane, east flower market, Beijing

