

New design security automatic swing barrier turnstile gate for entrance control

Our Product Introduction

Basic Information

- Place of Origin: 00
- Brand Name: 2
- Certification: 3
- Minimum Order Quantity: 100
- Packaging Details: 付款方式
- Delivery Time: 供 能力
- Payment Terms: 期限
- Supply Ability: 常 包装



Product Specification

- Lane Width: 550-570mm
- IP: IP54
- Pass Speed: 30 Persons/min
- Power Supply: AC220V/110V,50/60Hz
- Drive Mode: Motor Drive
- Max Power Consumption: 200W
- Opening Time: 0.3S
- Humidity: ≤90% Coagulation Free
- Noise: ≤50dB
- Service Life: 5,000,000 Cycles
- Outside Packing: 150x110x42 Cm
- Working Environment: -20°C~+60°C
- Metal: Type Iron
- Thickness: 203*193*15cm
- Box Type: Self Erecting Boxes



Product Description

New design security automatic swing barrier turnstile gate for entrance control

Product description:

This equipment is integrated with mechanism, electric and micro-controller and various kinds of identification technologies, compatible with IC, ID, bar code, fingerprint reader and so on to provide intelligent control and management to flow control. Durable, anti-rusty. provide orderly passage to people, anti-illegal entry or exit, smooth operation, low noise. arm drops off in condition of emergencies.

Product features:

1. Problem-self-checking function.
2. Arm Turning: Bi-direction.
3. When power off, the arm open automatically, and power on again, the arm will be held automatically.
4. When a valid card is read and the passenger passed, the arm can be delayed to close from 1-60s which can be set in the control panel.
5. Auto-reposition function: After the card is read, the passenger doesn't pass within the regulated time, and the turnstile will cancel the order automatically. And the regulated time can be set by managers.
6. Anti-rush function: if there is no open single, the arm will be held tightly.
7. Stable running with little noise.

Product specification:

Material	304stainless steel
Specification	1200*280*990mm
work voltage	AC220V±10% 50HZ±10%
Core	DC24V solenoid valve
Size	1200*280*990mm
Arm length	500mm
Max bearing force	80KG
Max lane width	550MM
Rotation direction for arm	left or right, or bi-directional Led direction indicator
Card reading window	standard or customized

Product advantages:

1. he speed gate turnstile is with high-quality DC brushless motor is configured and advanced servo control system is carried to truly achieve precise control, stable performance with no maintenance.
2. Lossless mechanism structure is based on German technology adopted to ensure long lifespan.

FAQ:

Q: Did you system have software interface?

A: Yes. We have our own management software.

Q: How does this system connect the access control?

A: Equipment could link to others by TCP/IP or Wiegand.

Q: Does ticket barcode supported?

A: Yes, many access control method for options. Customized management support.

Q: What will happened if power was cut off?

A: The barrier will open automatically if power cut off.

Q: Is it difficult to install it?

A: Its easy to install and we will offer the installation video.

Q: What is the strength of your company in this industry?

A: We are the top 5 in turnstile field in China, more than 120 employees and over 20 senior R & D technical persons to ensure the gate could work well in different environment, power supply and current. Experienced foreign trade business team can help you to deal with any emergency before, during and after the sales. The brand ZENTO is highly recognized in Southeast Asia.



Ellawig companies



+86-15399918960



service@ellawigss.com



ladyshairextensions.com

