

Hmi Touch Panel IP65 Monitor Industrial Rs485 Plc Intelligent UART Screen

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Minimum Order Quantity: 100

Ellawig companys

00

2

3

- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:

SIEMENS



Product Specification

- Warranty(Year):
- Brand Name:
- Type:
- Contrast Ratio:
- Certification:
- Series:
- Metal:
- Thickness:
- Box Type:
- Radiation Power:
- Metal Type:
- Universal Type:
- Indian Hair:
- Size:
- Hair Styles:

MOCHUAN

- Serial, Usb, Ethernet
- 1000:1

2-Year

- CE/FCC/ROHS
- For Business
- Type Iron
- 203*193*15cm
- Self Erecting Boxes
- 840~1300MW
- Iron
 - Fit For 80% Model Cars' Injectors
- Yes
 - 390x240x185cm
- Body Wave, Straight



for more products please visit us on ladyshairextensions.com

Hmi Touch Panel IP65 Monitor Industrial Rs485 Plc Intelligent UART Screen

Product description:

High brightness 1000 nits 21.5 inch square screen outdoor waterproof anti-glare monitor Viewing angle:40/40/50/50; 80/80/80/80;178/178; Display Colors 16.7M Brightness: 350-1500nits Touchscreen: Projected Capacitive Touch/ 5 Wire Resistive Touch/ Non-Touch DC12V/24V Operate Temperature:-10° to 60°C Storage: -20° to 70°C Aluminum Alloy Enclosure: Black and Silver color option, IP65 at Front bevel

Product details:

Backlight LED ≥20000H(Continuous working with maximum brightness, time of brightness halves) TA system:64 levels adjustment; DGI ISIIsystem:100 levels adjustment	Item	Parameter	Description			
Resolution 800*480 Support 0°/90°/180°/270°rotated display Backlight LED ≥20000H(Continuous working with maximum brightness, time of brightness halves) Brightness 170nit TA system:64 levels adjustment; DGUSIIsystem:100 levels adjustment. (It's not recommend to set brightness to 1%~30% of	Color	262k colors	18-bit 6R6G6B			
Backlight LED ≥20000H(Continuous working with maximum brightness, time of brightness halves) Brightness 170nit TA system:64 levels adjustment; DGUSIIsystem:100 levels adjustment. (It's not recommend to set brightness to 1%~30% of	Active Area (A.A.)	154.08mm (W)×85.92mm (H)	800*480			
Backlight LED brightness, time of brightness halves) Brightness TA system:64 levels adjustment; DGUSIIsystem:100 levels adjustment. (It's not recommend to set brightness to 1%~30% of	Resolution	800*480	Support 0°/90°/180°/270°rotated display			
Brightness 170nit DGUSIIsystem:100 levels adjustment. (It's not recommend to set brightness to 1%~30% of	Backlight	LED				
ine maximum, which may lead LOD licker)						
	blurring.Please ad	d				

the screensaver to avoid.

Voltage & Current:

Item	Conditions	Min	Тур	Max	Unit
Power Voltage	-	4.5	5.0	5.5	V
Operation Current	VCC = +5V, Backlight on	-	500	-	mA
(None Speaker)	VCC = +5V, Backlight off	-	170	-	mA
Recommended power su	ipply: 5V 1A DC				

Why Choose Us?

1. The Transaction record told our products is very popular and hot sale in European and American market.

2. Only keeping quality first and "Win-Win Situation" to help customer win and keep the market.

3. Mochuan Drives is worth your trust! Welcome contact us for price list.

FAQ:

Q: Are you a trading company or factory?

A: We are a professional industrial monitor/ panel/android touch screen PC manufacturer started from 2012.

Q: What's Minimum Order Quantity?

A: 1 pcs sample. You are welcomed to place order to test our product quality and services.

Q: What is your production time?

A: Different quantity, different production time. It will use about 9-12 days if your order over 500pcs.

Q: Are the pictures real picture?

A: The pictures of all products we sell are 100% real shoot, If you want to be our sales agent, you can cooperate with our company.

