

Waterproof 7 Inch HMI Touch Screen Panel LCD Support Cloud Servers

Our Product Introduction

for more products please visit us on ladyshairextensions.com

Basic Information

- Place of Origin: 00
- Brand Name: 2
- Certification: 3
- Minimum Order Quantity: 290
- Packaging Details: 付款方式
- Delivery Time: 供 能力
- Payment Terms: 期限
- Supply Ability: 常 包装



Product Specification

- Products Status: New, Stock
- Type: Resistive
- Brand Name: Maxtech
- Place Of Origin: Taiwan, China
- Application: For Business
- Function: Dustproof&Waterproof
- Metal: Type Iron
- Thickness: 203*193*15cm
- Box Type: Self Erecting Boxes
- Radiation Power: 840~1300MW
- Metal Type: Iron
- Universal Type: Fit For 80% Model Cars' Injectors
- Indian Hair: Yes
- Size: 390x240x185cm
- Hair Styles: Body Wave, Straight



Product Description

Waterproof 7 Inch HMI Touch Screen Panel LCD Support Cloud Servers

Product description:

The 7 inch LCD Touch Display (Model No. WTY070144A12LM) is of a color tft lcd display panel with 800x480 resolution and standard 50pin RGB interface, which support sunlight readable, high brightness, tape bonding, wide temperature. The touch panel is of a G+G structure capacitive touch panel, which is composed of a cover glass, sensor glass, driver IC and FPC. It is driven by a ILITEK IC Chip ILI2511, which utilizes an USB interface and supports 10 points touch.

Product details:

Item	Conditions	Min	Typ	Max	Unit
Working Temperature	60%RH at 5V voltage	-20	25	70	
Storage Temperature	-	-30	25	85	
Working Humidity	25	10%	60%	90%	RH
Protective Paint	-	-	None	-	-
Electrostatic protection capability	Air discharge	-	±4KV	-	-
	Contact discharge	-	±4KV	-	-
Group pulse	(CCS500)GB/T17626.4-2008 1KV 100KHz	-	2 Level	-	-

Interface

Item	Conditions	Min	Typ	Max	Unit
Baudrate	User Set	3150	115200	3225600	bps
Output Voltage (TXD)	Output 1, Iout = 1mA	3.0	3.3	-	V
	Output 0, Iout = -1mA	-	0	0.3	V
Input Voltage (RXD)	Input 1, Iout = 1mA	2.4	3.3	5.0	V
	Input 0, Iout = -1mA	0	-	0.5	V
Interface	UART2:N81,3.3V & 5V TTL/CMOS				
	UART4:Optional N81/E81/O81/N82 four mode,3.3V & 5V TTL/CMOS(Be used after OS configuration)				
Socket	10Pin_1.0mm FCC Socket				
Slot	YES (Micro SDHC(TF) card /FAT32 Format)				
USB	None				

Packaging & delivery

Quantity(pieces)	1 - 1	2 - 100	101 - 1000	>1000
Lead time (days)	7	14	21	To be negotiated

FAQ:

Question 1:

Does DWIN product need a MOQ when purchase? I only need some samples in the first.

Answer: No MOQ for standard product, and we have free sample for application, please scan below QR.

Question 2: What kind of Express are supported? Trade terms is ?

Answer: DHL, TNT, UPS, Fedex. Trade terms is EXW.



Ellawig companys



+86-15399918960



service@ellawigss.com



ladyshairextensions.com

Room 501, unit 6, building 20, North Lane, east flower market, Beijing